

Wire rope clips												
F mm	F "	A mm	E mm	H mm	I mm	L mm	R mm	S mm	g	Nm	N	
3	(1/8)	M4	12	18	9	20	7	10	9	1,25	3	
5	(3/16)	M5	13	24	13	24	10	15	20	2,46	3	
6	(1/4)	M6	15	27	15	28	11	16	33	4,24	3	
8	(5/16)	M6	19	31	17	34	12	18	40	4,24	5	
10	(3/8)	M8	22	37	20	42	13	21	79	10,20	5	
11	(7/16)	M8	22	41	22	44	14	24	79	10,20	5	
13	(1/2)	M10	33	44	25	55	15	26	130	20,11	5	
14	(9/16)	M10	33	47	27	57	18	27	145	20,11	5	
16	(5/8)	M10	33	51	29	6	20	28	175	20,11	5	
18	(11/16)	M12	44	56	34	75	21	32	260	34,43	5	
20	(3/4)	M12	44	62	34	75	22	33	290	34,43	5	
22	(7/8)	M12	52	65	39	85	25	35	340	34,43	7	
26	(1")	M14	50	72	42	95	27	40	490	54,77	7	
30	(1"1/8)	M14	50	78	47	110	33	43	620	54,77	8	
34	(1"1/4)	M16	55	88	53	120	37	48	840	85,14	8	
40	(1"1/2)	M16	60	98	59	140	40	54	1120	85,14	8	

Light wire rope clips									
F mm	A mm	E mm	H mm	I mm	L mm	R mm	S mm	g	
2	M3	10	17	7	17	6	10	7	
3	M3	12	18	8	21	6	10	18	
4	M4	13	21	10	23	8	11	25	
5	M5	13	25	12	25	10	13	32	
6	M6	18	28	14	32	12	16	65	
8	M6	18	31	16	35	15	18	80	
10	M8	23	38	20	44	18	20	120	
13	M10	26	47	25	55	23	26	160	
16	M10	32	54	28	68	29	28	260	

Thimbles light type							
F mm	B mm	C mm	H mm	R mm	S mm	T mm	g
2-3	16	9	16	5,5	0,6	45	2,3
4	19	11	18	6,5	0,7	60	3,0
5	24	14	22	7,5	0,8	75	5,0
6	28	17	26	9,0	1,0	90	8,0
8	33	19	30	12,0	1,2	168	15,0
10	38	21	34	14,5	1,5	210	23,0
12	44	30	46	16,0	1,8	252	44,0
14	49	33	50	18,5	2,0	294	61,0
16	57	40	59	21,0	2,0	336	83,0
18	68	46	69	24,0	2,5	378	135,0
20	78	51	77	27,0	3,0	540	215,0
22	88	56	84	28,0	3,0	594	225,0
25	92	60	91	31,0	3,5	675	330,0
28	109	75	115	39,0	4,0	924	575,0